



1.5 MIL TEDLAR® TAPE

DESCRIPTION: A thin, strong Tedlar® (polyvinyl fluoride) film coated with a patented "CW" acrylic adhesive system.

APPLICATIONS: Excellent where a high degree of resistance to UV light, direct exposure to sunlight and outdoor weathering, and exposure to a wide variety of chemicals is required.

TECHNICAL DATA

	<u>IMPERIAL</u>	<u>METRIC</u>
Thickness:	3.0 mils (.003")	0.076 mm
Peel Adhesion:		
(PSTC #1) off Stainless Steel	68 oz/inch width	19.2 N/2.5 cm
(PSTC #1) off Tedlar	68 oz/inch width	19.2 N/2.5 cm
Tensile:	11 lbs/inch width	49.8 N/2.5 cm
Elongation:	130%	130%
Low Temperature		
Application:	10°F	-12°C
High Temperature		
Resistance:	250°F	121°C
Low Environmental		
Resistance:	-10°F	-23°C
Water Vapor		
Transmission:	9-57 g/m ² (ASTM E-96 E-80)	
Release Liner:	55 lb polycoated	90 GSM
	natural kraft	
Color:	Gray	

**Tedlar® is a registered trademark of E.I. Dupont Co.

IMPORTANT INFORMATION:

The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using the product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods. 3/28/96

Accessible Products Company
2122 W. 5th Place
Tempe AZ 85281

480-967-8888 480-894-6255 F www.techlite.net